

Package ‘ENmix’

April 10, 2023

Title Quality control and analysis tools for Illumina DNA methylation BeadChip

Description Tools for quality control, analysis and visualization of Illumina DNA methylation array data.

Version 1.34.02

Imports grDevices,graphics,preprocessCore,matrixStats,methods,utils, geneplotter,impute,minfi,RPMM,illuminaio,dynamicTreeCut,IRanges,gtools, Biobase,ExperimentHub,AnnotationHub,genefilter,gplots,quadprog,S4Vectors

Depends parallel,doParallel,foreach,SummarizedExperiment,stats

Suggests minfiData, RUnit, BiocGenerics, BiocStyle, knitr, rmarkdown

biocViews DNAMethylation, Preprocessing, QualityControl, TwoChannel, Microarray, OneChannel, MethylationArray, BatchEffect, Normalization, DataImport, Regression, PrincipalComponent,Epigenetics, MultiChannel, DifferentialMethylation, ImmunoOncology

License Artistic-2.0

VignetteBuilder knitr

Encoding UTF-8

URL <https://github.com/Bioconductor/ENmix>

BugReports <https://github.com/Bioconductor/ENmix/issues>

NeedsCompilation no

Author Zongli Xu [cre,aut],
Liang Niu [aut] ,
Jack Taylor [ctb]

Maintainer Zongli Xu <xuz@niehs.nih.gov>

git_url <https://git.bioconductor.org/packages/ENmix>

git_branch RELEASE_3_16

git_last_commit faf0823

git_last_commit_date 2023-03-07

Date/Publication 2023-04-10

R topics documented:

B2M	2
calcdetP	3
combp	4
ctrlsva	5
dupicc	6
estimateCellProp	7
freqpoly	9
getB	10
getCGinfo	11
getmeth	12
ipdmr	13
M2B	14
methDataSet-class	15
methyAge	15
mhtplot	16
mprocess	18
multifreqpoly	20
nmode	21
norm.quantile	22
oxBS.MLE	23
p.qqplot	24
pcrplot	25
plotCtrl	26
predSex	27
preprocessENmix	28
qcfilter	30
QCinfo	31
rcp	33
readidat	34
readmanifest	36
relic	37
repicc	38
rgDataSet-class	40
simubed	40
Index	42

B2M

*Converting methylation beta value to M value.***Description**

Convert methylation beta value to M value.

Usage

B2M(x)

Arguments

x An numeric matrix with values between 0 and 1

Details

Methylation beta value is calculated as $\beta = M/(M+U+a)$. M is methylated intensity, U is unmethylated intensity, and a is a constant offset (by default, $a=100$). M value is calculated as $M = \log_2((M+a)/(U+a))$. M or U is usually greater than 1000, so a is negligible for most probes. if $a=0$, then $M = \log_2(\beta)/(1-\beta)$.

Value

A matrix of M values

Author(s)

Zongli Xu

Examples

```
if (require(minfiData)){
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path, recursive = TRUE)
  mdat = getmeth(rgSet)
  beta = getB(mdat, "Illumina")
  m = B2M(beta)
}
```

calcdetP

To calculate detection P values

Description

Calculation of detection P values based on negative internal control probes or out of the band (oob) probes

Usage

```
calcdetP(rgSet, detPtype = "negative")
```

Arguments

rgSet An object of class rgDataSet
detPtype Calculation of detection P values based on negative internal control ("negative") probes or out of the band ("oob") probes

Value

An numerical matrix of detection P values, with row for CpGs and column for samples

Author(s)

Zongli Xu

References

Wanding Zhou et al. SeSAME: reducing artifactual detection of DNA methylation by Infinium BeadChips in genomic deletions, *Nucleic Acids Research*, 2018

Examples

```
path <- file.path(find.package("minfiData"), "extdata")
rgSet <- readidat(path = path, recursive = TRUE)
detp=calcdetP(rgSet, detPtype = "negative")
detp2=calcdetP(rgSet, detPtype = "oob")
```

combp

Identification of differentially methylated regions

Description

To identify differentially methylated regions using a modified comb-p method

Usage

```
combp(data, dist.cutoff=1000, bin.size=310, seed=0.01,
      region_plot=TRUE, mht_plot=TRUE, nCores=10, verbose=TRUE)
```

Arguments

data	A data frame with colname name "chr", "start", "end", "p" and "probe", indicating chromosome (1,2,3,...,X,Y), chromosome start and end position, P value and probe names
dist.cutoff	Maximum distance in base pair to combine adjacent DMRs
bin.size	bin size for autocorrelation calculation
seed	FDR significance threshold for initial selection of DMR region
region_plot	If TRUE, regional plots will be generated
mht_plot	If TRUE, mahattan plot will be generated
nCores	Number of computer cores will be used in calculation
verbose	If TRUE, detailed running information will be printed

Details

The input should be a data frame with column names "chr", "start", "end", "p", and "probe", indicating chromosome number, start position, end position, P value and probe name. The function use a modified comb-p method to identify differentially methylated regions. DMR results will be stored in a file with name resu_combp.csv. If plot options were selected, two figure files will be generated: mht.jpg and region_plot.pdf.

Author(s)

Liang Niu, Zongli Xu

References

Pedersen BS1, Schwartz DA, Yang IV, Kechris KJ. Comb-p: software for combining, analyzing, grouping and correcting spatially correlated P-values. Bioinformatics 2012

Zongli Xu, Changchun Xie, Jack A. Taylor, Liang Niu, ipDMR: Identification of differentially methyl-ated regions with interval p-values, Bioinformatics 2020

Examples

```
dat=simubed()
names(dat)
#seed=0.1 is only for demonstration purpose, it should be smaller than 0.05 or 0.01 in actual study.
combp(data=dat,seed=0.1)
```

ctrlsva

Non-negative internal control surrogate variables

Description

Surrogate variables derived based on intensity data for non-negative internal control probes.

Usage

```
ctrlsva(rgSet,percvar=0.95,npc=1,flag=1)
```

Arguments

rgSet	An object of class rgDataSet or RGChannelSet.
percvar	Minimum percentage of data variations can be explained by surrogate variables, range from 0 to 1,default is 0.95
npc	Number of surrogate variables, default is 1
flag	1: select number of surrogate variables based on argument percvar; 2: select number of surrogate variables based on argument npc

Value

The function will return an numerical matrix with columns indicating surrogate variables and rows corresponding to samples. These variables can be used in association analysis to adjust for experimental batch effects.

Author(s)

Zongli Xu

References

Zongli Xu, Liang Niu, Leping Li and Jack A. Taylor, *ENmix: a novel background correction method for Illumina HumanMethylation450 BeadChip*. Nucleic Acids Research 2015.

Examples

```
if (require(minfiData)) {
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path, recursive = TRUE)
  sva <- ctrlsva(rgSet)
}
```

dupicc

Evaluation of measurement reliability using duplicate samples

Description

The function can be used to evaluate duplicate samples by calculating: 1) centered/un-centered Pearson's correlation coefficient between duplicates; 2) absolute difference between duplicates; 3) ICC for each CpG probes using oneway or twoway model.

Usage

```
dupicc(dat, dupid, mvalue=FALSE, center=TRUE, nCores=2, qcflag=FALSE, qc=NULL,
       detPthre=0.05, nbthre=3, skipicc=FALSE, corfig=FALSE, model="oneway")
```

Arguments

dat	Methylation beta value matrix
dupid	A data frame with two variables, id1 and id2. The two ids in each row indicate a duplicate pair. These ids should be the same with column names of the input methylation matrix
mvalue	If TRUE, the beta value will be converted to M value for calculation of ICC
center	If TRUE, the methylation beta values will be centered for each CpG before calculation of ICC or correlation
nCores	Number of cores will be used for calculation of ICC

qcflag	Whether to perform QC before calculation of ICC
qc	QC object from function QCinfo
detPthre	If qcflag=TRUE, the methylation values with detection P value higher than the threshold will be removed before calculation
nbthre	If qcflag=TRUE, the methylation values with number of bead smaller than the threshold will be removed
skipicc	If TRUE, ICC calculation will be skipped
corfig	If TRUE, a figure will be generated to demonstrate correlations within duplicates or within non-duplicates
model	Using "oneway" or "twoway" model to calculate ICC

Value

icc: a data frame containing ICC and P values for each probe

dupcor: a data frame containing Pearson's correlation and averaged absolute difference between duplicates.

Author(s)

Zongli Xu

References

Zongli Xu, Jack A Taylor. *Reliability of DNA methylation measures using Illumina methylation BeadChip*. Epigenetics 2020

Examples

```
if (require(minfiData)){
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path, recursive = TRUE)
  mdat=getmeth(rgSet)
  beta=getB(mdat, "Illumina")
  dupidx=data.frame(id1=c("5723646052_R02C02", "5723646052_R04C01", "5723646052_R05C02"),
  id2=c("5723646053_R04C02", "5723646053_R05C02", "5723646053_R06C02"))
  iccresu<-dupicc(dat=beta, dupid=dupidx)
}
```

estimateCellProp

Cell type proportion estimator

Description

To estimates relative proportion of underlying cell types in a sample based on reference methylation data of pure cell types.

Usage

```
estimateCellProp(userdata, refdata="FlowSorted.Blood.450k",
                 cellTypes=NULL, nonnegative = TRUE, nProbes=50,
                 normalize=TRUE, refplot=FALSE)
```

Arguments

userdata	The input can be <code>rgDataSet</code> , <code>methDataSet</code> , <code>MethylSet</code> , <code>RGChannelSet</code> or methylation beta value matrix.
refdata	Reference data set will used. Current option: "FlowSorted.Blood.450k", "FlowSorted.DLPFC.450k", "FlowSorted.CordBlood.450k", "FlowSorted.CordBloodCombined.450k", "FlowSorted.CordBloodNorway.450k" or "FlowSorted.Blood.EPIC".
cellTypes	Specific set of cell type data in reference data will be used for deconvolution. if "NULL" all cell types data will be used. see details for possible cell types
normalize	TRUE or FALSE, if TRUE, quantile normalization on methylated and unmethylated intensities will be performed.
nonnegative	TRUE or FALSE. If TRUE, the estimated proportions will be constrained to nonnegative values
nProbes	Number of best probes for each cell types will be used for the estimation.
refplot	TRUE or FALSE. IF TRUE, refdata distribution and heatmap will be plotted for inspection of reference dataset.

Details

This function use the method of Houseman et al (2012) to estimate cell type proportions based on reference DNA methylation data.

The following reference datasets can be used to assist the estimation. User should select a reference most resemble to user's data in tissue, age, and array type.

`FlowSorted.Blood.450k`: consisting of 450K methylation data for 60 blood samples from 6 male adults. Six samples for each of the cell types: Bcell CD4T CD8T Eos Gran Mono Neu NK PBMC WBC; See Reinius et al. 2012 for details.

`FlowSorted.CordBlood.450k`: consisting of 450k methylation data for 104 cord blood samples from 17 male and female individuals. Cell type (# samples) are: Bcell(15) CD4T(15) CD8T(14) Gran(12) Mono(15) NK(14) nRBC(4) WholeBlood(15). See Bakulski et al. Epigenetics 2016 for details.

`FlowSorted.CordBloodNorway.450k`: consisting of 450K methylation data for 77 cord blood samples from 11 individuals (6 girls and 5 boys). 11 samples for each of the cell types: Bcell CD4T CD8T Gran Mono NK WBC. See P Yousefi et al Environ. Mol. Mutagen 2015 for details.

`FlowSorted.Blood.EPIC`: consisting of EPIC methylation data for 37 magnetically sorted blood cell references from 12 individuals. See LA Salas et al. 2018 for details.

`FlowSorted.DLPFC.450k`: consisting of 450K methylation data for 58 brain tissue samples from 29 individuals. 15 females and 14 males, 6 Africans and 23 Caucasians, age range from 13 to 79. 29 samples for each of the cell types: NeuN_neg and NeuN_pos. See Guintivano et al. 2013 for details.

`FlowSorted.CordBloodCombined.450k`: consisting of 289 combined umbilical cord blood cells samples assayed by Bakulski et al, Gervin et al., de Goede et al., and Lin et al. see <https://github.com/immunomethylomics/FlowSorted.CordBloodCombined.450k> for details.

Value

The output is a data frame composed of the estimates of cell type proportions with columns indicate cell types and rows indicate samples.

Author(s)

Zongli Xu

References

EA Houseman, WP Accomando, DC Koestler, BC Christensen, CJ Marsit, HH Nelson, JK Wiencke and KT Kelsey. *DNA methylation arrays as surrogate measures of cell mixture distribution*. *BMC bioinformatics* (2012) 13:86.

Examples

```
require(minfiData)
path <- file.path(find.package("minfiData"), "extdata")
#based on rgDataset
rgSet <- readidat(path = path, recursive = TRUE)
celltype=estimateCellProp(userdata=rgSet, refdata="FlowSorted.Blood.450k",
                          nonnegative = TRUE, normalize=TRUE)
#using methDataSet
qc=QCinfo(rgSet)
mdat<-preprocessENmix(rgSet, bgParaEst="oob", dyeCorr="RELIC",
                      QCinfo=qc, nCores=6)
celltype=estimateCellProp(userdata=mdat, refdata="FlowSorted.Blood.450k",
                          nonnegative = TRUE, normalize=TRUE)
mdat<-norm.quantile(mdat, method="quantile1")
#using beta value
beta<-rcp(mdat, qcscore=qc)
celltype=estimateCellProp(userdata=beta, refdata="FlowSorted.Blood.450k",
                          nonnegative = TRUE)
```

freqpoly

Frequency polygon plot

Description

Similar to histogram, frequency polygon plot can be used to inspect data distribution.

Usage

```
freqpoly(mat, nbreaks=15, col="black", xlab="", ylab="Frequency",
         type="l", append=FALSE, ...)
```

Arguments

mat	A numeric vector
nbreaks	Number of bins for frequency counting
col	color code
xlab	x-axis lable
ylab	y-axis lable
type	character indicating the type of plotting; actually any of the 'type's as in 'plot.default'.
append	TRUE or FALSE, whether to create a new figure or append to the current figure.
...	Further arguments that get passed to the function "plot"

Value

Frequency polygon plot.

Author(s)

Zongli Xu

References

Zongli Xu, Liang Niu, Leping Li and Jack A. Taylor, *ENmix: a novel background correction method for Illumina HumanMethylation450 BeadChip*. Nucleic Acids Research 2015.

Examples

```
freqpoly(rnorm(1000))
```

getB *Extract methylation Beta values.*

Description

Extract Methylation Beta value, $Beta = Meth / (Meth + Unmeth + offset)$

Usage

```
getB(mdat, type="Illumina", offset=100)
```

Arguments

mdat	An object of class methDataSet or MethylSet.
type	type="Illumina" sets offset=100 as per Genome Studio software.
offset	Regularization factor in calculating beta ratio, 100 in default

Value

Methylation Beta value = Meth / (Meth + Unmeth + offset). Meth is methylated intensity matrix, Unmeth is unmethylated intensity matrix.

Author(s)

Zongli Xu

Examples

```
if (require(minfiData)){
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path, recursive = TRUE)
  mdat=getmeth(rgSet)
  beta=getB(mdat, "Illumina")
}
```

getCGinfo

CpG probe annotation information

Description

Extract CpG probe annotation information from an rgDataSet

Usage

```
getCGinfo(rgSet, type="IandII")
```

Arguments

rgSet	An object of class rgDataSet
type	One of the following options "I", "II", "IandII", "ctrl", indicating type I, type II type I & II or control probes type

Value

An object of data frame class

Author(s)

Zongli Xu

Examples

```
require(minfiData)
path <- file.path(find.package("minfiData"), "extdata")
#based on rgDataset
rgSet <- readidat(path = path, recursive = TRUE)
cginfo=getCGinfo(rgSet, type="IandII")
```

getmeth

Create a methDataSet

Description

To create a methDataSet based on a rgDataset

Usage

```
getmeth(rgSet)
```

Arguments

rgSet An object of class rgDataSet

Details

CpG annotation information is incorporated in the output methDataSet object, and can be extracted using command `rowData()`.

Value

An object of class methDataSet

Author(s)

Zongli Xu

Examples

```
require(minfiData)
path <- file.path(find.package("minfiData"), "extdata")
#based on rgDataset
rgSet <- readidat(path = path, recursive = TRUE)
meth=getmeth(rgSet)
meth
cginfo=rowData(meth)
```

ipdmr *Differentially methylated regions*

Description

To identify differentially methylated regions using an interval P value method

Usage

```
ipdmr(data, include.all.sig.sites=TRUE, dist.cutoff=1000, bin.size=50,  
seed=0.05, region_plot=TRUE, mht_plot=TRUE, verbose=TRUE)
```

Arguments

data	A data frame with colname name "chr", "start", "end", "p" and "probe", indicating chromosome (1,2,3,...,X,Y), chromosome start and end position, P value and probe names
include.all.sig.sites	Whether to use CpG singletons in calculation of FDR
dist.cutoff	Maximum distance in base pair to combine adjacent DMRs, and the maximum distance between CpGs where auto-correlation will be calculated
bin.size	bin size for autocorrelation calculation
seed	FDR threshold for initial selection of DMR regions
region_plot	If TRUE, regional plots will be produced for each DMR
mht_plot	If TRUE, a p-value mahattan plot with marked DMRs will be produced
verbose	Whether to output detailed information

Details

The input should be a data frame with column names "chr", "start", "end", "p" and "probe", indicating chromosome, start and end position, P value and probe name. The function will use a novel interval p value method to identify differentially methylated regions. DMR results will be stored in a file with name resu_ipdmr.csv. If plot options were selected, two figure files will be generated: mht.jpg and region_plot.pdf.

Author(s)

Liang Niu, Zongli Xu

References

Zongli Xu, Changchun Xie, Jack A. Taylor, Liang Niu, ipDMR: Identification of differentially methyl-ated regions with interval p-values, Bioinformatics 2020

Examples

```
dat=simubed()
names(dat)
#seed=0.1 is only for demonstration purpose, it should be smaller than 0.05 or 0.01 in actual study.
ipdmr(data=dat,seed=0.1) #seed=0.1
```

M2B*Converting methylation M value to beta value.*

Description

Converting methylation M value to methylation beta value.

Usage

```
M2B(x)
```

Arguments

x An numeric matrix

Details

Methylation beta value is calculated as $\text{beta} = M / (M + U + a)$. M is methylated intensity, U is unmethylated intensity, and a is a constant offset (by default , a=100). M value is calculated as $M = \log_2((M+a)/(U+a))$. M or U is usually greater than 1000, so a is negligible for most probes. if a=0, then $\text{beta} = 2^M / (2^M + 1)$.

Value

A matrix of methylation Beta values.

Author(s)

Zongli Xu

Examples

```
if (require(minfiData)){
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path, recursive = TRUE)
  mdat=getmeth(rgSet)
  beta=getB(mdat,"Illumina")
  m=B2M(beta)
  b=M2B(m)
}
```

methDataSet-class *Class "methDataSet"*

Description

A class for storing Illumina methylation array methylated and unmethylated intensity data, and CpG annotation information.

Usage

```
methDataSet(Meth = new("matrix"), Unmeth = new("matrix"),
            rowData=new("DataFrame"),...)
```

Arguments

Meth	A matrix of methylated intensity values with row for CpGs and column for samples
Unmeth	A matrix of unmethylated intensity values with row for CpGs and column for samples
rowData	A dataframe contains CpG annotation information
...	Other arguments for class SummarizedExperiment

Details

CpG annotation information is incorporated in the object, and can be extracted using command `rowData`

Value

An object of class `methDataSet`

Examples

```
showClass("methDataSet")
```

methyAge *Methylation Age estimator*

Description

To calculate Methylation Age using Hovath, Hannum or PhenoAge methods and pace of aging DunedinPACE.

Usage

```
methyAge(beta, fastImputation=FALSE, normalize=TRUE, nCores=2)
```

Arguments

beta	Methylation beta value matrix with CpG names(row names) and sample ids(column names).
fastImputation	If "TRUE" reference methylation values will used for imputation, if "FALSE", KNN nearest neighbor method will be used.
normalize	TRUE or FALSE, if TRUE, Horvath modified BMIQ method will be used to perform normalization.
nCores	Number of cores will be used for normalization

Value

A data frame with rows for sample and columns for types of methylation age.

Author(s)

Zongli Xu

References

Horvath S. *DNA methylation age of human tissues and cell types*. Genome biology 2013 14:R115.
 Hannum G, Guinney J, Zhao L, Zhang L, Hughes G, Sada S, et al. *Genome-wide methylation profiles reveal quantitative views of human aging rates*. Molecular cell 2013 49:359-367.
 Levine ME, Lu AT, Quach A, Chen BH, Assimes TL, Bandinelli S, et al. *An epigenetic biomarker of aging for lifespan and healthspan*. Aging (Albany NY) 2018 10:573-591.
 Daniel W Belsky, Avshalom Caspi, David L Corcoran, et al. *DunedinPACE, a DNA methylation biomarker of the pace of aging*. eLife, 2022

Examples

```
require(minfiData)
path <- file.path(find.package("minfiData"), "extdata")
#based on rgDataset
rgSet <- readidat(path = path, recursive = TRUE)
meth=getmeth(rgSet)
beta=getB(meth)
mage=methyAge(beta)
```

mhtplot

P value manhattan plot

Description

P value manhattan plot

Usage

```
mhtplot(probe=NULL,chr=NULL, pos=NULL, p=NULL,color="bg",sigthre=NULL,
sigthre2=NULL,threlty=c(2,1),markprobe=NULL,markcolor="red", outf="mht",
outfmt="jpg",reducesize=0)
```

Arguments

probe	probe name
chr	Chromosome, 1,2,...,22,X,Y
pos	Chromosome positions
p	P values
color	Color scheme of manhattan plot, "bg" indicate "black and gray"
sigthre	P value of significant threshold line
sigthre2	P value of second significant threshold line
threlty	Threshold line type, default is c(2,1)
markprobe	A list of CpGs to be marked out
markcolor	Color code for marked probe, "red" in default
outf	figure file name, default "mht"
outfmt	Output figure file format, "jpg" or "eps"
reducesize	A positive interger, larger the value, smaller the eps file size. Smaller file size is achieved by skipping some densely packed data points

Author(s)

Zongli Xu

Examples

```
dat=simubed()

thre1=1E-100
dat$fdr=p.adjust(mrgd$P, method="BH")
if(sum(dat$fdr<0.05)>0){thre1=max(dat$p[dat$fdr<0.05]}}

thre2=1E-7

mprobe=dat$probe[dat$p<=thre1]
mhtplot(probe=dat$probe,chr=dat$chr,pos=dat$start,p=dat$p,sigthre=thre1,sigthre2=thre2,
markprobe=mprobe,outf="mht_try",outfmt="jpg")
```

mprocess	<i>methylation data QC and preprocessing pipeline for Illuminal Bead-Chips</i>
----------	--

Description

The pipeline performs background correction, dye bias correction, inter-array normalization and probe type bias correction for HumanMethylation 450 and MethylationEPIC BeadChip data. It removes or mitigates background noise and systematic experimental bias. It also performs quality controls, identifying and excluding low quality samples and probes, removing low quality and outlier values, and performing imputation.

Usage

```
mprocess(rgSet, nCores=2, bgParaEst="oob", dyeCorr="RELIC",
         qc=TRUE, qnorm=TRUE, qmethod="quantile1",
         fqcfilter=FALSE, rmcr=FALSE, impute=FALSE)
```

Arguments

rgSet	An object of class rgDataSet, methDataSet, RGChannelSetExtended, RGChannelSet or MethylSet.
nCores	Number of cores will be used for computation
bgParaEst	Method to estimate background normal distribution parameters. Possible options: "oob", "est", or "neg".
dyeCorr	Dye bias correction, "mean": correction based on averaged red/green ratio; or "RELIC": correction with RELIC method; or "none": no dye bias correction. The default is RELIC
qc	If TRUE, QC will be performed. Low quality samples and CpGs will be excluded before background correction.
qnorm	If TRUE, inter-array quantile normalization will be performed.
qmethod	Quantile normalization method. This should be one of the following strings: "quantile1", "quantile2", or "quantile3". See details in function norm.quantile.
fqcfilter	If TRUE, outlier and low quality values will be filtered out.
rmcr	TRUE: excluded rows and columns with more than 5% of missing values. FALSE is in default
impute	Whether to impute missing values. If TRUE, k-nearest neighbor's methods will be used for imputation. FALSE is in default.

Details

Function mprocess is a pipeline that performs methylation data preprocessing and quality controls using functions: preprocessENmix, norm.quantile, rcp, QCinfo and qcfilter. More customized preprocessing steps can be achieved using the individual functions, see user's guide.

Value

A methylation beta value matrix with rows for CpGs and columns for samples.

Author(s)

Zongli Xu

References

Zongli Xu, Liang Niu, Leping Li and Jack A. Taylor, ENmix: a novel background correction method for Illumina HumanMethylation450 BeadChip. *Nucleic Acids Research* 2015.

Zongli Xu, Sabine A. S. Langie, Patrick De Boever, Jack A. Taylor¹ and Liang Niu, RELIC: a novel dye-bias correction method for Illumina Methylation BeadChip, *BMC Genomics*, 2017

Liang Niu, Zongli Xu and Jack A. Taylor: RCP: a novel probe design bias correction method for Illumina Methylation BeadChip, *Bioinformatics* 2016

See Also

Package `minfi` for classes [RGChannelSet](#) and [MethylSet](#)

Examples

```
if (require(minfiData)) {
  #rgDataSet as input
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path, recursive = TRUE)
  beta=mpreprocess(rgSet, nCores=6, qc=TRUE, fqcfilter=TRUE, rmcr=TRUE, impute=TRUE)

  #methDataSet as input
  mdat=getmeth(rgSet)
  beta=mpreprocess(mdat, nCores=6)

  #RGChannelSet as input
  beta=mpreprocess(RGsetEx, nCores=6)

  #RGChannelSetExtended as input
  sheet <- read.metharray.sheet(file.path(find.package("minfiData"), "extdata"),
    pattern = "csv$")
  rgSet <- read.metharray.exp(targets = sheet, extended = TRUE)
  beta=mpreprocess(rgSet, nCores=6, qc=TRUE, fqcfilter=TRUE, rmcr=TRUE, impute=TRUE)

  #MethylSet as input
  mdat=preprocessRaw(rgSet)
  beta=mpreprocess(mdat, nCores=6)
}
```

multifreqpoly

Multiple frequency polygon plot

Description

Produce Frequency polygon plot for each column of a numeric data matrix. Similar to multidensity function, the plot can be used to inspect data distribution but with much faster speed.

Usage

```
multifreqpoly(mat, nbreaks=100, col=1:ncol(mat), xlab="",  
              ylab="Frequency", legend = list(x = "top", fill=col,  
              legend = if(is.null(colnames(mat))) paste(1:ncol(mat))  
              else colnames(mat)), append=FALSE, ...)
```

Arguments

mat	A numeric matrix
nbreaks	The number of bins for frequency counting
col	Line plot color code, the length should be equal to the number of columns in mat
xlab	x-axis lable
ylab	y-axis lable
legend	A list of arguments that get passed to the function "legend"
append	TRUE or FALSE, whether to create a new figure or append to the current figure.
...	Further arguments that get passed to the function "plot"

Value

Frequency polygon plots.

Author(s)

Zongli Xu

References

Zongli Xu, Liang Niu, Leping Li and Jack A. Taylor, *ENmix: a novel background correction method for Illumina HumanMethylation450 BeadChip*. Nucleic Acids Research 2015.

Examples

```
x=matrix(rnorm(10000),nrow=2000,ncol=5)
multifreqpoly(x,nbreaks=15,legend=list(x="topright",fill=1:ncol(x),legend=paste("V",1:5,sep="")))

if (require(minfiData)) {
  path <- file.path(find.package("minfiData"),"extdata")
  rgSet <- readidat(path = path,recursive = TRUE)
  mraw <- getmeth(rgSet)
  beta<-getB(mraw)
  jpeg("dist_raw.jpg")
  multifreqpoly(beta,col=1:ncol(beta))
  dev.off()
}
```

nmode

Estimating number of mode for each row of data

Description

Due to SNPs in CpG probe region or other unknow factors, methylation beta values for some CpGs have multimodal distribution. This function is to identify this type of probes (so called gap probes) with obovious multimodal distribution.

Usage

```
nmode(x, minN = 3, modedist=0.2, nCores = 1)
```

Arguments

x	A methylation beta value matrix with row for probes and column for samples.
minN	Minimum number of data points at each cluster
modedist	Minimum distance between adjacent modes
nCores	Number of cores used for computation

Details

This function uses an empirical approach to estimate number of modes in methylation beta value for each CpG probe. By default, the function requires the distance between modes have to be greater than 0.2 in methylation beta value, and each mode clusters should has at least 3 data points or 5% of data points whichever is greater.

Value

A vector of integers indicating number of modes. Gap probes are probes with number of mode greater than 1.

Author(s)

Zongli Xu

References

Zongli Xu, Liang Niu, Leping Li and Jack A. Taylor, *ENmix: a novel background correction method for Illumina HumanMethylation450 BeadChip*. Nucleic Acids Research 2015

Examples

```
if (require(minfiData)) {
  mdat <- preprocessRaw(RGsetEx)
  beta=getBeta(mdat, "Illumina")
  nmode=nmode(beta, minN = 3,modedist=0.2, nCores = 5)

  path <- file.path(find.package("minfiData"),"extdata")
  rgSet <- readidat(path = path,recursive = TRUE)
  mdat <- getmeth(rgSet)
  beta=getB(mdat)
  nmode=nmode(beta, minN = 3,modedist=0.2, nCores = 5)
}
```

norm.quantile

Quantile normalization.

Description

Quantile normalization of methylation intensity data across samples for Illumina Infinium Human-Methylation 450 and MethylationEPIC BeadChip.

Usage

```
norm.quantile(mdat, method = "quantile1")
```

Arguments

mdat An object of class methDataSet or Methy1Set.
method Quantile normalization method: "quantile1", "quantile2", or "quantile3".

Details

By default, method = "quantile1", which will separately quantile normalize Methylated or Unmethylated intensities for Infinium I or II probes. The "quantile2" will quantile normalize combined Methylated or Unmethylated intensities for Infinium I or II probes. The "quantile3" will quantile normalize combined Methylated or Unmethylated intensities for Infinium I and II probes together.

Value

The output is an an object of class methDataSet or Methy1Set.

Author(s)

Zongli Xu

References

Pidsley, R., CC, Y.W., Volta, M., Lunnon, K., Mill, J. and Schalkwyk, L.C. (2013) A data-driven approach to preprocessing Illumina 450K methylation array data. BMC genomics, 14, 293.

Examples

```
#for methDataSet
path <- file.path(find.package("minfiData"), "extdata")
rgSet <- readidat(path = path, recursive = TRUE)
mdat<-preprocessENmix(rgSet, bgParaEst="oob", nCores=6)
mdatq<-norm.quantile(mdat, method="quantile1")

#for MethySet
if (require(minfiData)) {
  mdat=preprocessENmix(RGsetEx, bgParaEst="oob", nCores=6)
  mdatq=norm.quantile(mdat, method="quantile1")
}
```

 oxBS.MLE

oxBS-MLE.

Description

Maximum Likelihood Estimate (MLE) of 5-methylcytosine (5mC) and 5-hydroxymethylcytosine (5hmC) using sequencing/array data from paired bisulfite and oxidative bisulfite treated DNA experiments.

Usage

```
oxBS.MLE(beta.BS, beta.oxBS, N.BS, N.oxBS)
```

Arguments

beta.BS	A matrix of methylation beta values (proportion of methylated sites estimated as methylated intensity over total intensity) obtained from bisulfite (BS) experiments
beta.oxBS	A matrix of methylation beta values obtained from oxidative bisulfite (oxBS) experiments

N.BS	A matrix of total signals (sum of methylated and unmethylated intensity values) from BS experiments
N.oxBS	A matrix of total signals from oxBS experiments

Details

For all the inputs (beta.BS, beta.oxBS, N.BS and N.oxBS), the rows should be corresponding to CpG loci and the columns should be corresponding to samples. The row/column names in all four matrices should be the same. For a specific CpG of a sample, if any one of the four values (beta.BS, beta.oxBS, N.BS and N.oxBS) is NA, or N.BS is zero, or N.oxBS is zero, the MLE of both 5mC and 5hmC levels will be set as NA.

Value

The output is a list with two elements: 5mC: a matrix of estimated 5mC levels. 5hmC: a matrix for estimated 5hmC levels.

Author(s)

Liang Niu and Zongli Xu

References

Zongli Xu, Jack A. Taylor, Yuet-Kin Leung, Shuk-Mei Ho and Liang Niu, *oxBS-MLE: an efficient method to estimate 5-methylcytosine and 5-hydroxymethylcytosine in paired bisulfite and oxidative bisulfite treated DNA*, Bioinformatics. 2016

Examples

```
# load example data
load(system.file("oxBS.MLE.RData", package="ENmix"))
# run oxBS.MLE
resu<-oxBS.MLE(beta.BS,beta.oxBS,N.BS,N.oxBS)
dim(resu[["5mC"]])
dim(resu[["5hmC"]])
```

p.qqplot

P value Q-Q plot

Description

P value Q-Q plot with optional confidence interval

Usage

```
p.qqplot(pvalues, outf="qq", outfmt="jpg", draw.conf=TRUE,
          conf.col="lightgray", conf.alpha=.95, pch=20, col="black", reducesize=0)
```


Arguments

pvalues	An numeric vector of P values
outf	figure file name, default "qq"
outfmt	Output figure file format, "jpg" or "eps"
draw.conf	Whether to draw confidence interval of expected P values under NULL hypothesis
conf.col	Color code of confidence interval
conf.alpha	Confidence interval range, 0.95 in default
pch	Point type code
col	Point color code
reducesize	A positive interger, larger the value, smaller the eps file size. Smaller file size is achieved by skipping some densely packed data points

Details

P value Q-Q plot with optional confidence interval

Author(s)

Zongli Xu

Examples

```
dat=simubed()
p.qqplot(pvalues=dat$p,draw.conf=TRUE,outf="qq_try",outfmt="jpg")
```

pcrplot

Principal component regression plot

Description

First, principal component analysis will be performed in the standadized input data matrix (standadized for each row/CpG), and then the specified number of top principal components (which explain most data variation) will be used to perform linear regression with each specified variable. Regression P values will be plotted for exploration of methylation data variance structure or identification of possible confounding variables in association analysis.

Usage

```
pcrplot(beta, cov,npc=50,subset=TRUE,subsetsize=50000)
```

Arguments

beta	A methylation beta value matrix with rows for probes and columns for samples. The input matrix should not contain any missing value.
cov	A data frame of covariates. Categorical variables should be converted to factors. The number of rows should equal to the number of columns in beta matrix
npc	The number of top ranked principal components to be plotted
subset	If TRUE, a random subset probes will be used for the calculation
subsetsize	The size of a subset probes

Value

A jpeg figure "svdscreplot.jpg" to show the variations explained by each principal component.

A jpeg figure "pcr_diag.jpg" to show association strength between principal components and covariates with cell colors indicating different levels of association P values.

Author(s)

Zongli Xu

References

Zongli Xu, Liang Niu, Leping Li and Jack A. Taylor, *ENmix: a novel background correction method for Illumina HumanMethylation450 BeadChip*. Nucleic Acids Research 2015

Examples

```
if (require(minfiData)) {  
  mdat <- preprocessRaw(RGsetEx)  
  beta=getBeta(mdat, "Illumina")  
  group=pData(mdat)$Sample_Group  
  slide=factor(pData(mdat)$Slide)  
  cov=data.frame(group,slide)  
  pcrplot(beta,cov,npc=6)  
}
```

plotCtrl

Internal control plot

Description

The function will generate a series of internal control plots that are similar to the plots from Illumina GenomeStudio software. Users should refer to GenomeStudio online guide to interpret these figures. These figures can be used to check data quality and experimental procedures.

Usage

```
plotCtrl(rgSet, IDorder=NULL)
```

Arguments

rgSet	An object of class rgDataSet or RGChannelSet.
IDorder	A list of sample ids in the order specified by user. The list can be a subset of sample ids in input dataset. If an id list is provided, all plots will be produced in the order of the list.

Value

A set of internal control figures in jpeg format.

Author(s)

Zongli Xu

References

Zongli Xu, Liang Niu, Leping Li and Jack A. Taylor, *ENmix: a novel background correction method for Illumina HumanMethylation450 BeadChip*. Nucleic Acids Research 2015.

Examples

```
if (require(minfiData)) {  
  #rgDataSet as input  
  path <- file.path(find.package("minfiData"), "extdata")  
  rgSet <- readidat(path = path, recursive = TRUE)  
  plotCtrl(rgSet)  
  
  #RGChannelSet as input  
  pinfo=pData(RGsetEx)  
  IDorder=row.names(pinfo)[order(pinfo$Slide, pinfo$Array)]  
  plotCtrl(RGsetEx, IDorder)  
}
```

predSex

Estimating sample sex

Description

Estimating sample sex based on methylation data

Usage

```
predSex(mdat, cutoff = 2)
```

Arguments

mdat	An object of class MethDataSet or rgDataSet.
cutoff	The difference in log2 total intensity between X and Y chromosomes

Details

Estimation of sex is based on the difference of log2 median total intensity measures on the X and Y chromosomes.

Author(s)

Zongli Xu

Examples

```
if (require(minfiData)) {
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path, recursive = TRUE)
  sex=predSex(rgSet)
}
```

```
preprocessENmix
```

```
The ENmix background correction
```

Description

The ENmix background correction for HumanMethylation 450 and MethylationEPIC BeadChip. ENmix models methylation signal intensities with a flexible exponential-normal mixture distribution, and models background noise with a truncated normal distribution. ENmix will split BeadChip intensity data into 6 parts and separately model methylated and unmethylated intensities, 2 different color channels and 2 different probe types.

Usage

```
preprocessENmix(rgSet, bgParaEst = "oob", dyeCorr="RELIC", QCinfo=NULL, exQCsample=TRUE,
  exQCcpg=TRUE, exSample=NULL, exCpG=NULL, nCores = 2)
```

Arguments

rgSet	An object of class rgDataSet, methDataSet, RGChannelSetExtended, RGChannelSet or MethylSet.
bgParaEst	Method to estimate background normal distribution parameters. Options are: "oob", "est", or "neg".
dyeCorr	Dye bias correction method, "mean": correction based on averaged red/green ratio, or "RELIC": correction with RELIC method (default method), or "none": no dye bias correction.

QCinfo	If QCinfo object from function QCinfo() is provided, low quality samples (if exQCsample=TRUE) and CpGs (if exQCcpg=TRUE) will be excluded before background correction.
exQCsample	If TRUE, low quality samples listed in QCinfo will be excluded.
exQCcpg	If TRUE, low quality CpGs listed in QCinfo will be excluded.
exSample	User specified samples to be excluded before background correction
exCpG	User specified probes to be excluded before background correction
nCores	Number of cores will be used for computation

Details

By default, ENmix will use out-of-band Infinium I intensities ("oob") to estimate normal distribution parameters for modeling background noise. Option "est" will use combined methylated and unmethylated intensities to estimate background distribution parameters separately for each color channel and each probe type. Option "neg" will use 600 chip internal controls probes to estimate background distribution parameters. If rgSet is a Methy1Set, then only option "est" can be selected.

Value

An object of class same with input data

Author(s)

Zongli Xu and Liang Niu

References

Zongli Xu, Liang Niu, Leping Li and Jack A. Taylor, ENmix: a novel background correction method for Illumina HumanMethylation450 BeadChip. *Nucleic Acids Research* 2015.

Zongli Xu, Sabine A. S. Langie, Patrick De Boever, Jack A. Taylor1 and Liang Niu, RELIC: a novel dye-bias correction method for Illumina Methylation BeadChip, *BMC Genomics*. 2017

Examples

```
if (require(minfiData)) {
  #rgDataSet as input
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path, recursive = TRUE)
  #quality control information
  qc<-QCinfo(rgSet)
  #further excluding samples which are not in the qc$badsample list
  ex_id=c("5723646053_R04C02")
  #further excluding cpgs which are not in the qc$badCpG list
  ex_cg=c("cg00000622", "cg00001245", "cg00001261")
  mdat=preprocessENmix(rgSet, QCinfo=qc, exSample=ex_id, exCpG=ex_cg, nCores=6)

  #RGChannelSet as input
```

```
mdat=preprocessENmix(RGsetEx,nCores=6)
}
```

qcfilter
Filtering out low quality and outlier data

Description

Outlier was defined as values smaller than 3 times IQR from the lower quartile or greater than 3 times IQR from the upper quartile. If data quality information were provided, low quality data points will be set as missing data first before looking for outliers. All outliers and low quality data will be set as miss in output matrix. If set `impute=TRUE`, imputation will be performed using k-nearest neighbors method to impute all missing values.

Usage

```
qcfilter(mat,qcscore=NULL,rmoutlier=TRUE,byrow=TRUE,detPthre=0.000001,nbthre=3,
         rmc=False,rthre=0.05,cthre=0.05,impute=False,imputebyrow=TRUE,fastimpute=False,...)
```

Arguments

<code>mat</code>	An numeric matrix containing methylation beta values
<code>qcscore</code>	If the data quality information (the output from function <code>QCinfo</code>) were provided, low quality data points as defined by detection p value threshold (<code>detPthre</code>) and number of bead threshold (<code>nbthre</code>) will be set as missing value.
<code>rmoutlier</code>	if <code>TRUE</code> , outliers data points will be set as missing data <code>NA</code> .
<code>byrow</code>	<code>TRUE</code> : Looking for outliers row by row, or <code>FALSE</code> : column by column.
<code>detPthre</code>	Detection P value threshold to define low quality data points, <code>detPthre=0.000001</code> in default.
<code>nbthre</code>	Number of beads threshold to define low quality data points, <code>nbthre=3</code> in default.
<code>rmcr</code>	<code>TRUE</code> : exclude rows and columns with too many missing values as defined by <code>rthre</code> and <code>cthre</code> . <code>FALSE</code> is in default
<code>rthre</code>	Minimum of percentage of missing values for a row to be excluded
<code>cthre</code>	Minimum of percentage of missing values for a column to be excluded
<code>impute</code>	If <code>TRUE</code> , k-nearest neighbors methods will used for imputation.
<code>imputebyrow</code>	<code>TRUE</code> : impute missing values using similar values in row, or <code>FALSE</code> : in column
<code>fastimpute</code>	If <code>TRUE</code> , probe median will be used for fast imputation.
<code>...</code>	Arguments to be passed to the function <code>impute.knn</code> in R package "impute"

Value

The output is an numeric matrix.

Author(s)

Zongli Xu

References

Zongli Xu, Liang Niu, Leping Li and Jack A. Taylor, *ENmix: a novel background correction method for Illumina HumanMethylation450 BeadChip*. Nucleic Acids Research 2015.

Examples

```
if (require(minfiData)) {
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path, recursive = TRUE)
  qc=QCinfo(rgSet)
  mdat=preprocessENmix(rgSet, QCinfo=qc, nCores=6)
  mdat=norm.quantile(mdat, method="quantile1")
  beta=rcp(mdat)
  #filter out outliers data points only
  b1=qcfilter(beta)
  #filter out low quality and outlier data points
  b2=qcfilter(beta, qcscore=qc)
  #filter out low quality and outlier values, remove rows and columns with
  # too many missing values
  b3=qcfilter(beta, qcscore=qc, rmcr=TRUE)
  #filter out low quality and outlier values, remove rows and columns with
  # too many missing values, and then do imputation
  b3=qcfilter(beta, qcscore=qc, rmcr=TRUE, impute=TRUE)
}
```

QCinfo

Extract QC information

Description

Extract information for data quality control: detection P values, number of beads and averaged bisulfite conversion intensity. The function can also identify low quality samples and probes, as well as outlier samples in total intensity or beta value distribution.

Usage

```
QCinfo(rgSet, detPthre=0.000001, detPtype="negative", nbthre=3, samplethre=0.05,
       CpGthre=0.05, bisulthre=NULL, outlier=TRUE, distplot=TRUE)
```

Arguments

rgSet	An object of class rgDataSet, or RGChannelSetExtended
detPthre	Detection P value threshold to identify low quality data point
detPtype	Calculate detection P values based on negative internal control ("negative") probes or out of the band ("oob") probes
nbthre	Number of bead threshold to identify data point of low quality
samplethre	Threshold to identify samples with low data quality, the percentage of low quality methylation data points across probes for each sample
CpGthre	Threshold to identify probes with low data quality, percentage of low quality methylation data points across samples for each probe
bisulthre	Threshold of bisulfite intensity for identification of low quality samples. By default, Mean - 3 x SD of sample bisulfite control intensities will be used as a threshold.
outlier	If TRUE, outlier samples in total intensity or beta value distribution will be identified and classified as bad samples.
distplot	TRUE or FALSE, whether to produce beta value distribution plots before and after QC.

Value

detP: a matrix of detection P values

nbead: a matrix for number of beads

bisul: a vector of averaged intensities for bisulfite conversion controls per sample

badsample: a list of low quality or outlier samples

badCpG: a list of low quality CpGs

outlier_sample: a list of outlier samples in methylation beta value or total intensity distribution.

Figure "qc_sample.jpg": scatter plot of Percent of low quality data per sample vs. Average bisulfite conversion intensity

Figure "qc_CpG.jpg": histogram for Percent of low quality data per CpG.

Figure "freqpolygon_beta_beforeQC.jpg": distribution plot of input data, samples colored in red are "bad" samples, list in badsample, including samples with low data quality and outlier in methylation beta value or total intensity.

Figure "freqpolygon_beta_afterQC.jpg": distribution plot input data after filtering "bad" samples.

Author(s)

Zongli Xu

References

Zongli Xu, Liang Niu, Leping Li and Jack A. Taylor, *ENmix: a novel background correction method for Illumina HumanMethylation450 BeadChip*. Nucleic Acids Research 2015.

Examples

```

if (require(minfiData)) {
  #rgDataSet as input
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path, recursive = TRUE)
  qc=QCinfo(rgSet)

  #RGChannelSetExtended as input
  sheet <- read.metharray.sheet(file.path(find.package("minfiData"), "extdata"),
    pattern = "csv$")
  rgSet <- read.metharray.exp(targets = sheet, extended = TRUE)
  qc<-QCinfo(rgSet)
}

```

rcp

Illumina methylation array probe type bias correction

Description

Probe design type bias correction using Regression on Correlated Probes (RCP) method

Usage

```
rcp(mdat, dist=25, quantile.grid=seq(0.001,0.999,by=0.001), qcscore = NULL,
  nbthre=3, detPthre=0.000001)
```

Arguments

mdat	An object of class methDataSet or MethylSet.
dist	Maximum distance in base pair between type I and type II probe pairs for regression calibration
quantile.grid	Quantile grid used in linear regression
qcscore	Data quality information object, the output from function QCinfo. If the object is provided, low quality data points as defined by detection p value threshold (detPthre) or number of bead threshold (nbthre) will be set as missing values.
detPthre	Detection P value threshold to define low quality data points
nbthre	Number of beads threshold to define low quality data points, nbthre=3 in default.

Details

The function will first identify type I and type II probe pairs within a specified distance, and then perform linear regression calibration between the probe types. With the estimates the function will then adjust type II data using type I data as references.

Value

A beta value matrix

Author(s)

Liang Niu, Zongli Xu

References

Liang Niu, Zongli Xu and Jack A. Taylor *RCP: a novel probe design bias correction method for Illumina Methylation BeadChip*, *Bioinformatics* 2016

Examples

```
if (require(minfiData)) {
#methDataSet as input
path <- file.path(find.package("minfiData"),"extdata")
rgSet <- readidat(path = path,recursive = TRUE)
qc=QCinfo(rgSet)
mdat=preprocessENmix(rgSet,QCinfo=qc,nCores=6)
mdat=norm.quantile(mdat,method="quantile1")
beta=rcp(mdat)

#methylset as input
sheet <- read.metharray.sheet(file.path(find.package("minfiData"),"extdata"),
  pattern = "csv$")
rgSet <- read.metharray.exp(targets = sheet,extended = TRUE)
qc=QCinfo(rgSet)
mdat=preprocessENmix(rgSet,QCinfo=qc,nCores=6)
mdat=norm.quantile(mdat,method="quantile1")
beta=rcp(mdat)
}
```

readidat

Parsing IDAT files for Illumina methylation arrays .

Description

Read in IDAT files and create a rgDataSet with probe annotation

Usage

```
readidat(path = NULL,manifestfile=NULL,recursive = TRUE, verbose = FALSE, force=FALSE)
```

Arguments

path	Directory where idat files are located
manifestfile	Array manifestfile, which can be downloaded from Illumina website. Bioconductor manifest package will be used if not provided
recursive	if TRUE, idat files in the subdirectories will also be read in
verbose	if TRUE, detailed running info will be printed on screen
force	if TRUE, arrays with different sizes will be merged together

Details

Some array types and corresponding manifestfiles can be guessed by the program based on the number of probes per array. However, we recommend to provide correct manifest file directly, which can be easily downloaded from Illumina website, see below for some examples.

Probe annotation info can be extracted using command `rowData`

Value

An object of class `rgDataSet`,

Author(s)

Zongli Xu

Examples

```
#Illumina methylation array manifestfile

#Infinium Mouse Methylation Manifest File (CSV)
system("wget https://support.illumina.com/content/dam/illumina-support/documents/downloads/productfiles/mouse-methylation-manifest-file-csv.zip")
system("unzip infinium-mouse-methylation-manifest-file-csv.zip")
mf="infinium-mouse-methylation-manifest-file.csv"

#for MethylationEPIC v1.0 B5
system("wget https://webdata.illumina.com/downloads/productfiles/methylationEPIC/infinium-methylationepic-v1-0-b5-manifest-file-csv.zip")
system("unzip infinium-methylationepic-v1-0-b5-manifest-file-csv.zip")
mf="infinium-methylationepic-v1-0-b5-manifest-file.csv"
manifest=readmanifest(mf)

#for MethylationEPIC v1.0 B4
system("wget https://webdata.illumina.com/downloads/productfiles/methylationEPIC/infinium-methylationepic-v1-0-b4-manifest-file-csv.zip")
system("unzip infinium-methylationepic-v1-0-b4-manifest-file-csv.zip")
mf="MethylationEPIC_v1-0_B4.csv"
manifest=readmanifest(mf)

#for HumanMethylation450
system("wget https://webdata.illumina.com/downloads/productfiles/humanmethylation450/humanmethylation450_150174-manifest-file-csv.zip")
system("unzip humanmethylation450_150174-manifest-file-csv.zip")
mf="humanmethylation450_150174-manifest-file.csv"
manifest=readmanifest(mf)
```

```
mf="HumanMethylation450_15017482_v1-2.csv"

mf="HumanMethylation450_15017482_v1-2.csv"
if(require(minfiData)){
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path,manifestfile=mf,recursive = TRUE)

  #without providing manifest file, corresponding R manifestfile package will be used
  rgSet <- readidat(path = path,recursive = TRUE)
}
```

readmanifest

Parsing Illumina methylation arrays manifest file.

Description

Parsing Illumina methylation arrays manifest file.

Usage

```
readmanifest(file)
```

Arguments

file Illumina methylation array manifest file, downloaded from Illuminal website

Value

An object of dataframe caintaining probe annotation information

Author(s)

Zongli Xu

Examples

```
#for MethylationEPIC v1.0 B5
system("wget https://webdata.illumina.com/downloads/productfiles/methylationEPIC/infinium-methylationepic-v1-0-b5-manifest-file-csv.zip")
system("unzip infinium-methylationepic-v1-0-b5-manifest-file-csv.zip")
mf="infinium-methylationepic-v1-0-b5-manifest-file.csv"
manifest=readmanifest(mf)

#for MethylationEPIC v1.0 B4
system("wget https://webdata.illumina.com/downloads/productfiles/methylationEPIC/infinium-methylationepic-v1-0-b4-manifest-file-csv.zip")
system("unzip infinium-methylationepic-v1-0-b4-manifest-file-csv.zip")
mf="MethylationEPIC_v1-0_B4.csv"
manifest=readmanifest(mf)

#for HumanMethylation450
```

```
system("wget https://webdata.illumina.com/downloads/productfiles/humanmethylation450/humanmethylation450_15017482_v1-2.csv")
mf="HumanMethylation450_15017482_v1-2.csv"
manifest=readmanifest(mf)
```

relic

REgression on Logarithm of Internal Control probes (RELIC)

Description

REgression on Logarithm of Internal Control probes (RELIC) correct for dye bias on whole array by utilizing the intensity values of paired internal control probes that monitor the two color channels.

Usage

```
relic (mdat,at_red,cg_grn)
```

Arguments

mdat	An object of class methDataSet or MethylSet.
at_red	an intensity matrix for Illumina control probes "NORM_A" and "NORM_T"
cg_grn	an intensity matrix for Illumina control probes "NORM_C" and "NORM_G"

Details

The Illumina MethylationEPIC BeadChip contains 85 pairs of internal normalization control probes (name with prefix NORM_A, NORM_T, NORM_G or NORM_C), while its predecessor, Illumina HumanMethyl-ation450 BeadChip contains 93 pairs. RELIC first performs a regression on the logarithms of the intensity values of the normalization control probes to derive a quantitative relationship between red and green channels, and then uses the relationship to correct for dye-bias on intensity values for whole array.

Value

An object of class methDataSet or MethylSet depends on input class.

Author(s)

Zongli Xu and Liang Niu

References

Zongli Xu, Sabine A. S. Langie, Patrick De Boever, Jack A. Taylor and Liang Niu, RELIC: a novel dye-bias correction method for Illumina Methylation BeadChip, BMC Genomics. 2017

See Also

Package preprocessENmix

Examples

```

if (require(minfiData)) {

##background correction and dye bias correction
#rgDataSet as input
path <- file.path(find.package("minfiData"), "extdata")
rgSet <- readidat(path = path, recursive = TRUE)
mdat <- preprocessENmix(rgSet, bgParaEst="oob", nCores=6, dyeCorr ="RELIC")

#RGChannelSet as input
mdat=preprocessENmix(RGsetEx, bgParaEst="oob", nCores=6, dyeCorr ="RELIC")

##dye bias correction only
#methDataSet as input
path <- file.path(find.package("minfiData"), "extdata")
rgSet <- readidat(path = path, recursive = TRUE)
ctrls <- getCGinfo(rgSet, type="ctrl")
ctrls <- ctrl[ctrls$Address %in% rownames(rgSet),]

ctrl_r <- assays(rgSet)$Red[ctrls$Address,]
ctrl_g <- assays(rgSet)$Green[ctrls$Address,]
CG.controls <- ctrl$Type %in% c("NORM_C", "NORM_G")
AT.controls <- ctrl$Type %in% c("NORM_A", "NORM_T")
cg_grn=ctrl_g[CG.controls,]
at_red=ctrl_r[AT.controls,]
rownames(cg_grn) = ctrl$ExtendedType[CG.controls]
rownames(at_red) = ctrl$ExtendedType[AT.controls]
mdat=getmeth(rgSet)
mdat <- relic(mdat, at_red, cg_grn)

#MethylSet as input
ctrls <- getProbeInfo(RGsetEx, type="Control")
ctrls <- ctrl[ctrls$Address %in% featureNames(RGsetEx),]
ctrl_r <- getRed(RGsetEx)[ctrls$Address,]
ctrl_g <- getGreen(RGsetEx)[ctrls$Address,]
CG.controls <- ctrl$Type %in% c("NORM_C", "NORM_G")
AT.controls <- ctrl$Type %in% c("NORM_A", "NORM_T")
cg_grn <- ctrl_g[CG.controls,]
at_red <- ctrl_r[AT.controls,]
rownames(cg_grn) = ctrl$ExtendedType[CG.controls]
rownames(at_red) = ctrl$ExtendedType[AT.controls]
mdat <- preprocessRaw(RGsetEx)
mdat <- relic(mdat, at_red, cg_grn)

}

```

Description

The function can be used to calculate ICC for each CpG probe using balanced or unbalanced replicate samples.

Usage

```
repicc(dat,repid,mvalue=FALSE,nCores=2,qcflag=FALSE,qc=NULL,
       detPthre=0.05,nbthre=3)
```

Arguments

dat	Methylation beta value matrix
repid	A data frame with two variables, id and idx. id should be the same with column name of "dat", idx is a variable to show the relationship between samples with same value for samples from same individual.
mvalue	If TRUE, the beta value will be converted to M value for calculation of ICC
nCores	Number of cores will be used for calculation of ICC
qcflag	Whether to perform QC before calculation of ICC
qc	QC object from function QCinfo
detPthre	If qcflag=TRUE, the methylation values with detection P value higher than the threshold will be removed before calculation
nbthre	If qcflag=TRUE, the methylation values with number of bead smaller

Value

A data frame containing ICC for each probe

Author(s)

Zongli Xu

References

Zongli Xu, Jack A Taylor. *Reliability of DNA methylation measures using Illumina methylation BeadChip*. Epigenetics 2020

Examples

```
if (require(minfiData)){
  path <- file.path(find.package("minfiData"), "extdata")
  rgSet <- readidat(path = path,recursive = TRUE)
  mdat=getmeth(rgSet)
  beta=getB(mdat,"Illumina")
  repid=data.frame(id=c("5723646052_R02C02", "5723646052_R04C01", "5723646052_R05C02", "5723646053_R04C02", "5723646053_R05C02"),
  iccresu<-repicc(dat=beta,repid=repid)
}
```

rgDataSet-class	Class "rgDataSet"
-----------------	-------------------

Description

A class for storing Illumina methylation array raw intensity data of two color channels, and probe annotation information.

Usage

```
rgDataSet(Red = new("matrix"), Green = new("matrix"),
  NBeads = new("matrix"), rowData=new("DataFrame"), ictrl= new("DataFrame"),...)
```

Arguments

Red	A matrix of Red channel intensity values with row for methylation probes and column for samples
Green	A matrix of Green channel intensity values with row for methylation probes and column for samples
NBeads	A matrix contains the number of beads used to generate intensity values on the Red and Green channels.
rowData	A dataframe contains probe annotation information
ictrl	A dataframe contains detailed information for Illumina internal control probes
...	other arguments for class SummarizedExperiment

Value

An object of class rgDataSet

Examples

```
showClass("rgDataSet")
```

simubed	Simulation of bed format example file.
---------	--

Description

Simulation of bed format example file.

Usage

```
simubed(nprobe=1000)
```


Arguments

nprobe Number of probes on each chromosome, default is 1000

Details

Simulation of bed format example file.

Value

A data frame

Author(s)

Zongli Xu

Examples

```
simubed(nprobe=1000)
```

Index

B2M, 2

calcdetP, 3
combp, 4
ctrlsva, 5

dupicc, 6

estimateCellProp, 7

freqpoly, 9

getB, 10
getCGinfo, 11
getmeth, 12

ipdmr, 13

M2B, 14
methDataSet (methDataSet-class), 15
methDataSet-class, 15
methyAge, 15
MethylSet, 19
mhtplot, 16
mpreprocess, 18
multifreqpoly, 20

nmode, 21
norm.quantile, 22

oxBS.MLE, 23

p.qqplot, 24
pcrplot, 25
plotCtrl, 26
predSex, 27
preprocessENmix, 28

qcfilter, 30
QCinfo, 31

rcp, 33

readidat, 34
readmanifest, 36
relic, 37
repicc, 38
RGChannelSet, 19
rgDataSet (rgDataSet-class), 40
rgDataSet-class, 40

show, methDataSet-method
 (methDataSet-class), 15
show, rgDataSet-method
 (rgDataSet-class), 40
simubed, 40